

SYNTHETIC AUTOMOTIVE ENGINE OILS

These Synthetic engine oils has been formulated to meet the latest car manufacturer's warranty requirements and designed to meet the demands of small displacement, high RPM fuel efficient engines found in today's domestic and foreign automobiles. A blend of high quality synthetics and specialized additives provide maximum protection against high temprature oxidation, wear, rust, corrosion, viscosity breakdown while keeping your engine exceptionally clean and free of sludge and varnish. It also helps protect against the increasing impact of low-speed pre-ignition (LSPI) in turbocharged gasoline direct injection engines (GDI). Contact your Industrial Account Representative for European spec information.

SAE GRADE	0W20	5W20	5W30	10W30
DENSITY (D4052) KG/M@ 15°C	N/A	N/A	N/A	N/A
KINEMATIC VISCOSITY (D445) CST @ 40°C	44.8	52.5	58.2	63.6
KINEMATIC VISCOSITY (D445)CST @ 100°C	8.6	9	10.5	10.7
VISCOSITY INDEX (D2270)	175	156	173	155
CCS VISCOSITY (D2602) CP @ -35°C	N/A	N/A	N/A	N/A
CCS VISCOSITY (D2602) CP @ -30°C	N/A	N/A	N/A	N/A
CCS VISCOSITY (D2602) CP @ -25°C	N/A	N/A	N/A	N/A

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC AUTOMOTIVE ENGINE OILS

SAE GRADE	0W20	5W20	5W30	10W30
FLASH POINT (D92), °C	230	232	234	235
POUR POINT (D97), °C	-49	-45	-43	-40
COLOUR (ASTM)	N/A	N/A	N/A	N/A
ASH SULPHATE, MASS%	N/A	N/A	N/A	N/A

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

- RECOMMENDED PASSENGER VEHICLES, LIGHT DUTY PICK UPS, MOTOR CYCLES AND OTHER GASOLINE ENGINES.
- EXCEEDS API SERVICE CLASSIFICATION SP
- MEETS AND EXCEEDS THE REQUIREMENTS FOR GM 6094M, CHRYSLER MS-6395 N, FORD WSS-M2C 929-A, WSS-M2C 9306-A, WSS-M26946-A
- RECOMMENDED FOR DOMESTIC AND FOREIGN HIGH PERFORMANCE ENGINES, ESPECIALLY SMALL HIGH RPM AND TURBO CHARGED ENGINES
- EXCEEDS ILSAC GF-6A REQUIREMENTS
- MEETS OR EXCEEDS GENERAL MOTORS REQUIRING DEXOS I

*NOTE: NOT RECOMMENDED FOR HEAVY DUTY CRITICAL TRUCK ENGINES

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

