

INDUSTRIAL GEAR OIL

Industrial gear oils are formulated to prevent rust, oxidation and corrosion by combining them with extreme pressure and anti foam agents to make them optimal oils for gear performance.

SAE GRADE	68	100	150	220	320	460
API GRAVITY	2EP	3EP	4EP	5EP	6EP	7EP
KINEMATIC VISCOSITY (D445) CST @ 40°C	68	100	150	220	320	460
KINEMATIC VISCOSITY (D445) CST @ 100°C	9.6	11.4	14.8	18.8	24.1	30.7
VISCOSITY INDEX (D2270)	92	95	95	95	95	96
FLASH POINT (D92), °C	197	233	243	267	287	283
POUR POINT (D97), °C	-35	-35	-28	-23	-23	-9

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- AGMA: 250.4
- US STEEL 224

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

