

SYNTHETIC GL-4 GEAR OIL

Specifically designed to meet the service requirements of API: GL-4. This synthetic gear oil is formulated for superior flow ability, to minimize gear wear, reduce frictional drag and protect against heavy loading failures in extreme weather conditions.

| SAE GRADE | 75W90 |
|--|--------------|
| DENSITY @ 15.5°C, KG/L | 0.8762 |
| KINEMATIC VISCOSITY (D445) CST @ 40°C | 92.32 |
| KINEMATIC VISCOSITY (D445) CST @ 100°C | 15.42 |
| VISCOSITY INDEX (D2270) | 141 |
| FLASH POINT (D92), °C | 204 |
| POUR POINT (D97), °C | -48 |
| BROOKFIELD VISCOSITY @ -40°C | 133000 |

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: GL-4
- SAE: 75W90

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

