

## FAST FLOW HYDRAULIC OIL

BOSS Fast Flow Hydraulic Oils are formulated with an excellent anti-wear additives packages for operational use in low and high-pressure systems in industrial and mobile applications. These industrial grade hydraulic oils are designed for heavy duty applications encountered in industry. These products have superior thermal stability and oxidation characteristics as well as excellent demulsibility, extreme pressure, rust protection and low filter blockage tendency.

ISO GRADE	22	32	46	68
DENSITY @ 15°C, KG/L	0.86	0.8614	0.865	0.8694
KINEMATIC VISCOSITY CST @ 40°C	22	32	46	68
KINEMATIC VISCOSITY CST @ 100°C	4.2	5.4	6.8	8.9
VISCOSITY INDEX	100	100	105	102
FLASH POINT, °C	179	190	232	232
POUR POINT, °C	-42	-36	-33	-30
DEMULSIBILITY (D1401)	PASS	PASS	PASS	PASS
OXIDATION STABILITY (D943), HRS	3000	4000	4000	4000
COLOR	PALE	PALE	PALE	PALE

### APPLICATIONS

- DENSION HF-1, HF-2, HF-0
- EATON/VICKERS I-286-S, M-2950-S

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*





## FAST FLOW HYDRAULIC OIL

### APPLICATIONS

- CINCINNATI MACHINE P-68, P-69, P-70
- RACINE, VARIABLE VOLUME VANE PUMP

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

