



MATERIAL SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product/Chemical Name: BOSSAMATIC Synthetic Automatic Transmission Fluid

Product Description: Lubricating Oil

Chemical Formula: Mixture

Chemical Family: Hydrocarbon

Manufacturer:

BOSS LUBRICANTS

112, 6303 -30 ST SE

Calgary, AB

T2C 1R4

Issue Date: January 1st 2015

Information: 1-800-844-9457

Emergency: 1-800-844-9457

www.bosslubricants.com

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>Percentages (by weight)</u>	<u>PEL (OSHA)</u>	<u>TLV (ACGIH)</u>	<u>CAS#</u>
Oil, Solvent Neutral Mixtures	70-80	N/A	5mg/m ³ TWA (oil mist)	

Performance Additives: Proprietary

(TWA: time Weighted Average is the employee's average airborne exposure in any 8-hour work shift of a 40- hour work week which shall not be exceeded)

(STEL: Short Term Exposure Limit is the employee's 15-minute time weighted average exposure which shall not be exceeded at any time during a work day unless another time is specified.

SECTION 3: HAZARDOUS IDENTIFICATION

Emergency Overview: Potential Health Effects

Routes of Entry: Eye Contact, Dermal, Inhalation.

Acute Effects of Overexposure;

Eyes: Contact with eyes may cause irritation.

Skin: Contact with skin may cause irritation.

Inhalation: May cause irritation of the nose and throat.

Ingestion: May cause nausea and vomiting. Large quantities may affect the central nervous system.

Chronic Effects of Overexposure: No adverse effects anticipated.

Medical Conditions Aggravated by Exposure: Existing dermatitis and respiratory conditions.

Carcinogenicity: NTP: No

IARC: No

OSHA: No



INDEPENDENT LUBRICANT
MANUFACTURERS ASSOCIATION





SECTION 4: FIRST AID MEASURES

Emergency and First Aid Procedures:

Eye Contact: If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15 minutes, occasionally lifting the lower and upper lids. Get medical attention.

Skin Contact: If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If irritation persists after washing, get medical attention immediately.

Inhalation: If person breathes in large amounts of material, move the exposed person to fresh air. If breathing has stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as possible.

Ingestion: If material has been swallowed, do not induce vomiting. Get medical attention immediately.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point: 350°F (>177°C)

Auto Ignition Temp: > 500°F

Flammable Limits in Air

% by volume

Lower

Upper

N/A

N/A

Extinguishing Media: Use the water spray to cool the fire exposed surface, and to protect personnel. Use foam, dry chemical or water spray (fog) to extinguish fire.

Special Fire Fighting Procedures: When fighting fires wear full turnout gear and self-contained breathing apparatus. Water may cause splattering. Material floats on water.

Unusual Fire and Explosion Hazards: Toxic fumes gases or vapors may evolve on burning.

Hazard Ratings:

NFPA 704:

Health: 1

Fire: 1

Reactivity: 0

HMIS':

Health:

Fire:

Reactivity:

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to take if Material is Released or Spilled:

Personal protective equipment should be worn. Ventilate area if confined or poorly ventilated. Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. This may require evacuation of severely contaminated soil. Avoid contact with skin and eyes.



SECTION 7: HANDLING AND STORAGE

Handling and Storage:

Store in a closed container kept away from all ignition sources. Handling temperatures should not exceed 175°F (80°C). Wash thoroughly after handling. Do not store at temperatures exceeding 113°F (45°C). Odorous and toxic fumes may form from the decomposition of this product if stored at excessive temperatures for extended periods of time. Open containers carefully and only in well ventilated areas or use appropriate respiratory protection. Store in a well ventilated area.

SECTION 8: EXPOSURE CONTROL – PERSONAL PROTECTION

Engineering Controls: Ventilate to control mists and vapors below exposure limits.

Respiratory Equipment: Normally not required, if exposure limits are exceeded use a Niosh approved organic vapor respirator. Self-contained breathing apparatus is recommended for entry into confined spaces or other poorly ventilated areas and for large spill clean-up sites.

Eye Protection: Chemical goggles or face shield recommended minimizing eye contact.

Protective Clothing: Impervious (nitrile) gloves recommended when handling material to minimize exposure. Long sleeve shirts, chemically protective aprons and chemically protective boots are recommended for contact exposure or spill clean-up. Do not wear watches, rings or similar apparel that could entrap the material next to the skin.

Other (Safety Showers, Eyes Wash Station etc...): Water should be available for flushing and washing when exposure exists. Launder soiled clothes. Discard shoes or other leather articles saturated with the material.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	Red Liquid, Mild petroleum odor
Boiling Point:	N/D
Specific Gravity (water=1):	0.8443 – 0.8649
Vapor Pressure:	<1mm Hg 68°F
Vapor Density (air=1):	N/D
Soluble in Water:	Insoluble
pH:	N/D
Evaporation Rate (ether= 1) :	<1



SECTION 10: STABILITY AND REACTIVITY

Stability:

Stable: At room temperature and pressure. See handling and storage section

Incompatibility:

Conditions to Avoid: See handling and storage section.

Materials to Avoid: Acids, oxidizing agents.

Hazardous Decomposition Products: Smoke, carbon monoxide, aldehydes, hydrogen sulfide, and alkyl mercaptans may be released. Under combustion conditions, oxides of the following elements will be formed: Magnesium, calcium, nitrogen, sulfur, and carbon.

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Note: BOSS Lubricants has not conducted specific toxicity tests on this product.

SECTION 12: ECOLOGICAL INFORMATION

Note: BOSS Lubricants has not conducted specific ecological tests on this product.

SECTION 13: DISPOSABLE CONSIDERATIONS

Waste Disposal Procedures: Place contaminated materials in a disposable container and dispose of in accordance with Local, State and Federal environmental regulations.

SECTION 14: TRANSPORT INFORMATION

DOT Proper Shipping Name: N/A

DOT Hazard Class: N/A

DOT Identification Number: N/A

DOT Emergency Response Guide Number: N/A

SECTION 15: REGULATORY INFORMATION

This product (does/not) contain toxic chemicals subject to the reporting requirements of SARA Section 13 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS Number

N/A

Chemical Name

N/A

Percent by Weight

N/A

Sara Section 311-312 Hazard Categories (40 CFR 370.2): Immediate health

Fire: No

Sudden Release of Pressure: No

Reactive: No

Acute: Yes

Chronic: No



INDEPENDENT LUBRICANT
MANUFACTURERS ASSOCIATION





SECTION 16: OTHER INFORMATION

Date: July1, 2015

The information contained in the MSDS relates only to the specific material identified. It does not cover the use of that material in combination with any other material or in any particular process. In compliance with 29 C.F.R. 1910.1200(g), BOSS Lubricants has prepared this MSDS in segments, with the intent that those segments be read together as a whole without textual omissions or alterations. BOSS Lubricants believes the information contained herein to be accurate, but makes no representation, guarantee, or warranty, express or implied, about the accuracy, reliability, or completeness of the information or about the fitness of contents herein for either general or particular purposes. Persons reviewing this MSDS should make their own determination as to the material's suitability and completeness for use in their particular application.