

MULTI VEHICLE SYNTHETIC BLEND ATF

This advanced additive formulation system which uses specific selected synthetic and mineral base oils while possessing a shear-stable polymer to provide exceptional friction and anti-shudder durability, improving low temperature operability and resistance to oxidation, rust and thermal degradation. This blend meets the stringent wear, friction and operational requirements of most automatic transmissions for a smooth driving experience.

TYPICAL PROPERTIES	MV ATF
SPECIFIC GRAVITY @ 15°C	0.8598
KINEMATIC VISCOSITY CST @ 40°C	35.43
KINEMATIC VISCOSITY CST @ 100°C	7.56
VISCOSITY INDEX (D2270)	189
BROOKFIELD VISCOSITY @ -40°C	11000
FLASH POINT (D92), °C	N/A
POUR POINT (D97), °C	-51
COLOUR	RED

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- MAN 339 TYPE Z1, Z2, V1
- MERCON V (XT-5-QM, XT-5-DM)

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



MULTI VEHICLE SYNTHETIC BLEND ATF

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- ZF TE-ML 14B

SUITABLE FOR USE IN:

- AUDI G 052 025, 052 162, 055 025
- BMW P/N 83 22 0 024 359, ETL-8072B
- BMW P/N 83 22 0 403 249, ETL-8072B
- BMW P/N 83 22 9 407 807, LT 711 41
- DEXRON III G/H, DEXRON II, DEXRON, AW1
- VOLVO P/N 1161540-8
- CHRYSLER AS68RC, DIAMOND SP-III
- CHRYSLER P/N 68043742AA (DEX VI)
- JWS 3309, ANY 3309
- MAZDA ATF M-III, MV, T-IV
- SUZUKI 3314, 3317
- FORD P/N XT-2-SM (SYN MERC)
- NISSAN MATIC-D, J, K, 402
- SHELL 3403, LA2634, TEXACO 7045-E, ETL-8072B
- ESSO 71141
- BMW P/N 83 22 0 0246 922, ETL-7045E
- BMW P/N 83 22 9 407 765, LA 2634
- BMW 7045E, LA2634, LT71141
- HONDA DW-1, Z-1
- HYUNDAI/KIA/MITSUBISHI DIAMOND SP-II & SP-III, RED-1, SP-IV
- CHRYSLER P/N 05127382AA
- IDEMITSU K17
- M315-2004 JASO 1A, 2A
- MB236.1,2,5,6,7,9,10,11
- FORD P/N XT-2-DX (MERC)
- MERCON, FORD ESP-M2C166-H
- TEXACO N402
- HYUNDAI NSWS9638

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



MULTI VEHICLE SYNTHETIC BLEND ATF

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- FUCHS 3353
- MINI P/N 83 22 0 402 413
- SAAB P/N 22 717 466, 93 165 147 (AW-1)
- PORSCHE P/N 999 917 547 00 (A2)
- SHELL 3403 M115
- TOYOTA T-II, T-III, T-IV, WS, FORD, XT8QAW
- JWS 3324
- VOLVO PASSENGER CAR (4-6 SP)
- VW G 052 025, 162, 099, 055 025
- IDEMITSU APOROIL ATF HP
- SATURN P/N21005966
- JAGUAR P/N WSS-M2C922-A-1
- VW P/N GUS000 162
- SUBARU ATF, ATF-HP
- SATURN T-IV, GM-TASA, T-IV ATF, GM WS ATF
- VOITH 55.6335 (G607)
- VOLVO 97340, 97341
- ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

