

## SYNTHETIC GL-5 GEAR OIL

Specifically designed to meet the service requirements of API: GL-5 , Eaton and Rockwell differentials. Formulated for superior flow ability to minimize gear wear, reduce frictional drag and protect against heavy loading failures in extreme weather conditions.

SAE GRADE	75W90 w/Limited Slip	75W140	80W140
DENSITY @ 15.5°C, KG/L	0.8695	0.8835	0.8835
KINEMATIC VISCOSITY (D445) CST @ 40°C	109.3	175.1	175.1
KINEMATIC VISCOSITY (D445) CST @ 100°C	16.5	24.85	24.85
VISCOSITY INDEX (D2270)	159	175	175
FLASH POINT (D92), °C	204	202	216
POUR POINT (D97), °C	-51	-51	-51
BROOKFIELD VISCOSITY @-40°C	135000	105000	105000

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: GL-5
- MACK: GO-J, GO-H, GO-G

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



## SYNTHETIC GL-5 GEAR OIL

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- MT-1
- AIST/US STEEL 224
- SAE: J2360, MIL-2105E/F
- LIMITED SLIP
- ROCKWELL: 076-E
- AGMA 9005-E02: 250.03, 250.04, 251.02, NO. 4
- CEC: L-45-A-99

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

